



Dubbelgrind					
Öppning	Stolpe A/B	K	L	J	M
DG 2000	A=120x120x3	2450mm	2150mm	2050mm	1250mm
DG 3000	A=120x120x3	3450mm	3150mm	3050mm	1750mm
DG 4000	A=120x120x3	4450mm	4150mm	4050mm	2250mm
DG 5000	A=120x120x3	5450mm	5150mm	5050mm	2750mm
DG 6000	B=150x150x6	6480mm	6180mm	6080mm	3250mm
DG 7000	B=150x150x6	7480mm	7180mm	7080mm	3750mm
DG 8000	B=150x150x6	8480mm	8180mm	8080mm	4250mm
DG 9000	B=150x150x6	9480mm	9180mm	9080mm	4750mm
DG 10000	B=150x150x6	10480mm	10210mm	10080mm	5250mm
DG 11000	B=150x150x6	11480mm	11180mm	11080mm	5750mm
DG 12000	B=150x150x6	12480mm	12180mm	12080mm	6250mm

Fundamentstättning för Heras slaggrind dubbel.
 Typ: HDA 212.
 Serie: DGT120120EL.
 Betongkvalitet C 25/30
 Fundamentsdjupet bör beaktas vid speciella markförhållande.



NO.3
 AP
 2021-06-07
 Ingjutning Slag DG