



Dubbelgrind	Hängslås	Spanjolett	Hängslås	Spanjolett	Hängslås	Spanjolett	
Öppning	K	(K)	J	(J)	M	(M)	P
DG 2000	2270mm	2300mm	2060mm	2090mm	1190mm	1220mm	300mm
DG 3000	3270mm	3300mm	3060mm	3090mm	1690mm	1720mm	300mm
DG 3500	3770mm	3800mm	3560mm	3590mm	1940mm	1970mm	300mm
DG 4000	4270mm	4300mm	4060mm	4090mm	2190mm	2220mm	300mm
DG 4500	4770mm	4800mm	4560mm	4590mm	2440mm	2470mm	300mm
DG 5000	5270mm	5300mm	5060mm	5090mm	2690mm	2720mm	300mm
DG 5500	5770mm	5800mm	5490mm	5520mm	2940mm	2970mm	400mm
DG 6000	6270mm	6300mm	5990mm	6020mm	3190mm	3220mm	400mm
DG 6500	6770mm	6800mm	6490mm	6520mm	3440mm	3470mm	400mm
DG 7000	7270mm	7300mm	6990mm	7020mm	3690mm	3720mm	400mm
DG 7500	7770mm	7800mm	7490mm	7520mm	3940mm	3970mm	400mm
DG 8000	8270mm	8300mm	8020mm	8050mm	4190mm	4220mm	400mm
DG 8500	8770mm	8800mm	8520mm	8550mm	4440mm	4470mm	400mm
DG 9000	9270mm	9300mm	9020mm	9050mm	4690mm	4720mm	400mm
DG 9500	9770mm	9800mm	9520mm	9550mm	4940mm	4970mm	400mm
DG 10000	10270mm	10300mm	10020mm	10050mm	5190mm	5220mm	400mm
DG 10500	10770mm	10800mm	10520mm	10550mm	5440mm	5470mm	400mm
DG 11000	11270mm	11300mm	11020mm	11050mm	5690mm	5720mm	400mm
DG 11500	11770mm	11800mm	11520mm	11550mm	5940mm	5970mm	400mm
DG 12000	12270mm	12300mm	12020mm	12050mm	6190mm	6220mm	400mm

Fundamentsritning för Heras slaggrind dubbel.  
 Typ: HD 812.  
 Serie: DGT120120man.  
 Betongkvalitet C 25/30  
 Fundamentsdjupet bör beaktas vid speciella markförhållande.



NO:3  
 AP  
 2021-06-16  
 Ingjutning Slag DG manuell